



WHITE GREASE

HIGH-QUALITY MULTI-FUNCTIONAL GREASE BASED ON PTFE



TECHNICAL SPECIFICATIONS

Chemical base:	Lithium and calcium grease with mineral oils and P.T.F.E.
Colour:	White
Minimum temperature resistance:	-30 °C
Maximum temperature resistance:	125 °C

STORAGE CONDITIONS

Shelf life: At least 36 months after production.

Stored in unopened packaging between +5°C and +25°C.

Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

PRODUCT DESCRIPTION

High-quality multi-functional grease based on PTFE.

FIELD OF APPLICATION

For lubrication and protection of all types of sliding, ball and roller bearings, shafts, chains, gears, hinges and other rotating parts. Mechanically very stable at high pressure and high operating temperatures.

PROPERTIES

- Resistant to high mechanical and thermal loads
- Rust and corrosion resistant
- Water resistant
- Water repellent
- Acid-free
- With extra precision spray hose

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

APPLICATION

Directions for use:

Shake well before use.

Spray surface(s) evenly from a distance of approx. 10-20 cm.

Points of attention: Use the additional spray hose integrated in the cap for optimum dosage.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.