



# POLY MAX® HIGH TACK V-NOZZLE

## FOR PROCESSING POLY MAX® HIGH TACK EXPRESS IN SAUSAGE PACKAGING.



### PRODUCT DESCRIPTION

Nozzle with special V-opening for processing Poly Max® High Tack Express in sausage packaging. For use in combination with Poly Max® Sausage Gun.

### FIELD OF APPLICATION

Tool for processing Poly Max® High Tack Express in sausage packaging.

### PROPERTIES

Nozzle with V-opening for applying an optimal adhesive strip:

- for perfect even distribution of the adhesive
- for an extra high initial bond strength

### APPLICATION

#### Directions for use:

1. Turn sealing ring off front side of sausage gun.
2. Click High Tack V-nozzle into sealing ring.
3. Press and hold Direct Stop and pull the metal rod backwards.
4. Place sausage in sausage gun.
5. Cut open sausage immediately after closing bob e.g. with a pair of pliers.
6. Turn sealing ring back on sausage gun.
7. Press Direct Stop again and push rod against the sausage.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.