



WOOD LUBRICANT

SILICONE-FREE LUBRICANT, GREASE AND PROTECTION AGENT FOR WOODWORKING MACHINES

STORAGE CONDITIONS

A minimum of 24 months.

Store in properly sealed packaging in a dry place at between +5°C and +25°C.



PRODUCT DESCRIPTION

Transparent, silicone-free lubricant, grease and protection agent for woodworking machines.

FIELD OF APPLICATION

For woodworking machines, such as sawing and milling machines, planers and spindles, gears and guide rails. Leaves no residue. Prevents the adhesion of resin. After processing wood can be painted, pickled and bonded.

PROPERTIES

- Silicone-free
- Ideal lubricating film
- Protects
- Lubricates
- Rust and corrosion resistant
- Durable
- Resistant to temperatures between -50°C and +120°C
- Transparent
- Can be used in all positions

APPLICATION

Directions for use:

Remove dust, sawdust, moisture etc. Shake can well before use. Spray surface evenly from a distance of approx. 25 cm.

TECHNICAL SPECIFICATIONS

| | |
|------------------|------------------------|
| Chemical base: | Various oils |
| Colour: | Transparent grey |
| Density approx.: | 0.81 g/cm ³ |

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.