1233109 - GRIFFON VASELINE POT 200 G NL/FR/EN/ES



ACID-FREE MAINTENANCE AND PROTECTION GREASE



TECHNICAL SPECIFICATIONS

Acid free:	Yes
Chemical base:	Acid-free vaseline
Colour:	White
Density approx.:	0.81 g/cm ³
Minimum temperature resistance:	-20 °C
Maximum temperature resistance:	45 °C
Viscosity:	Pasty

STORAGE CONDITIONS

Shelf life: At least 36 months after production. Stored in unopened packaging between +5°C and +25°C. Best Before Date (MM/YY): see packaging. Close packaging properly after use and store in a dry, cool, and frost-free location. Limited shelf life after opening.

PRODUCT DESCRIPTION

Acid-free maintenance and protection grease.

FIELD OF APPLICATION

For maintenance and protection of metal, such as (garden) tools, bolts and nuts, hinges and battery terminals, against oxidation and corrosion.

PROPERTIES

- · Pharmaceutical quality
- · Rust and corrosion resistant
- · Water resistant
- · Acid-free
- · Silicone-free

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

APPLICATION

Directions for use: Coat surface thinly and evenly.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.