



SPRAY ADHESIVE

AROMATIC-FREE, UNIVERSAL, LIQUID SPRAY ADHESIVE BASED ON SBR RUBBER.



PRODUCT DESCRIPTION

For mutual bonding or temporary fixation of paper, cardboard, felt, fabric, cork, polystyrene foam, polyurethane foam and metal foils and to surfaces made of wood, hardboard, chipboard, glass, concrete and metal. Highly suitable for temporary fixation of templates

FIELD OF APPLICATION

For bonding paper, cardboard, collages, metal foils, leather, felt, many plastics, textiles, Styrofoam® etc. with themselves and many other materials such as wood, ceramics, glass etc. Not suitable for PE, PP.

PROPERTIES

- Bonds immediately
- Aromatics-free
- Universal
- Moisture resistant

PREPARATION

Working Conditions: Do not use at temperatures below +10 °C.

Personal safety: Spray adhesive contains volatile, highly flammable solvents. Appropriate precautions should be taken when using and storing this product. When applying product to larger surfaces, ensure good ventilation in the working area.

Surface Requirements: The areas to be glued must be dry and free of any dust or grease.

APPLICATION

Coverage: 5 m²/l, applied on both sides

Directions for use:

Shake Aerosol well before use. Temporary fixation: 1) Apply adhesive thinly and evenly to one of the surfaces from a distance of approx. 25 cm. 2) Allow to dry for a minimum of 20 minutes. 3) Join materials and press firmly. Permanent bonding: 1) Apply adhesive thinly and evenly to both surfaces from a distance of approx. 25 cm. 2) Allow to dry for a minimum of 10 minutes. 3) Join materials and knock, roll or press together firmly. After spraying, hold the aerosol upside down and press the spray button until only propellant and no adhesive is emitted anymore. This prevents clogging of the aerosol.

Stains/residue: Wet adhesive residue can be removed using Griffon Cleaner. Dried adhesive residue can be removed mechanically or by using a paint stripper.

Advice: After spraying, hold the can upside down and press the aerosol until only propellant and no more glue comes out. This prevents the aerosol from clogging.

Points of attention: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Throw away only when completely empty. Do not breathe vapour. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – Do not smoke. Without adequate ventilation accumulation of potentially explosive alloys possible. Keep out of reach of children.

TECHNICAL SPECIFICATIONS

Chemical base:	Styrene-butadiene rubber (SBR)
Final bond strength after:	24 hours at 20°C
Handling time:	Bonds immediately
Maximum temperature resistance:	50 °C
Solid matter approx.:	22 %

STORAGE CONDITIONS

A minimum of 24 months.

Limited shelf life after opening.

Store in a dry, cool and frost free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.