



# COMBI SNEL

## TRANSPARENT, FAST, DUAL-COMPONENT EPOXY ADHESIVE



### Directions for use:

Remove the spatula from the side of the double syringe, and the closure cap from the handle. Break the seal of the double syringe. Press out an equal amount of both components. Mix these two equal parts well with the synthetic spatula. Apply the mixture, which at room temperature (+20°C) remains toolable for about 5 minutes, as a thin layer on one of the two materials. Assemble the material and keep it in place for 20 minutes. Be careful not to move the parts before the adhesive has cured. After use, clean the nozzle with a cloth and place the special cap in the handle on the double syringe. Resin and hardener must not come into contact with each other unless for usage.

**Stains/residue:** Remove wet adhesive residue immediately with warm water and soap. Dry adhesive residue can only be removed mechanically.

### TECHNICAL PROPERTIES

**Water resistance:** Good

**Filling capacity:** Good

### TECHNICAL SPECIFICATIONS

**Viscosity:** approx. 30000 mPa.s.

**Solid matter:** approx. 100 %

**Density:** approx. 1.16 g/cm<sup>3</sup>

### STORAGE CONDITIONS

A minimum of 24 months. Limited shelf life after opening. Store in a dry, cool and frost free place.

### PRODUCT DESCRIPTION

Transparent, fast, dual-component epoxy adhesive.

### FIELD OF APPLICATION

Ideal for fast, strong and invisible repair of many materials, both together and in combination, such as pottery, porcelain, glass, leather, wood, stone, metal and ceramics. Not suitable for bonding of PE, PTFE and silicone rubber.

### PROPERTIES

- Fast
- Strong
- Transparent
- Universal
- Filling
- Water resistant
- Chemical resistant
- Paintable

### PREPARATION

**Working conditions:** Only apply at temperatures between +5°C and +35°C. Product cures by mixing the resin and hardener.

**Personal safety:** It is recommended that rubber or plastic gloves are worn.

**Preliminary surface treatment:** Materials must be dry, clean and free of grease. Degrease parts to be bonded with Griffon Cleaner Kit or acetone. Roughen smooth surfaces (sandpaper).

### APPLICATION

**Coverage:** 240 cm<sup>2</sup> at a film thickness of 1 mm