



M-385

LIQUID, TRANSPARENT, WATERPROOF CONTACT ADHESIVE FOR BONDING PVC FOIL.



TECHNICAL SPECIFICATIONS

Chemical base:	TPU in solvent blend
Colour:	Transparent
Density approx.:	0,87 g/cm ³
Solid matter approx.:	16 %
Viscosity approx.:	2500 mPa·s

STORAGE CONDITIONS

Minimum of 24 months if stored in properly sealed packaging in a dry place at a temperature between +5°C and +25°C.

Limited shelf life after opening.

PRODUCT DESCRIPTION

Liquid, transparent, waterproof contact adhesive for bonding PVC foil.

FIELD OF APPLICATION

For mutually bonding PVC foils as well as for bonding PVC foil to hard PVC, rubber, canvas and wood such as for swimming pools, basins, ponds and roofs.

PROPERTIES

- High level of initial bonding
- Waterproof
- Plasticiser Resistant
- Permanently flexible
- Runny
- With brush
- With quick release cap

PREPARATION

Working Conditions: Do not use in temperatures $\leq +10^{\circ}\text{C}$.

APPLICATION

Directions for use:

1. Clean the surfaces to be bonded with Griffon Cleaner. 2. Apply adhesive thinly and evenly to both bonding surfaces and allow to dry for 3 to 12 minutes. 3. Join surfaces and press firmly. Remove excess adhesive. Properly close the container immediately after use.

Stains/residue: Remove adhesive stains with Griffon Cleaner and Cleaner Cloth.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.