

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

### 1 Identification

- **Product identifier**
- **Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41
- **Application of the substance / the mixture** Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Bison International  
Dr.A.F.Philipsstraat 9  
NL-4462 EW Goes  
PO Box 160  
NL-4460 AD Goes  
tel. +31 88 3235700  
fax. +31 88 3235800  
e mail: sds@boltonadhesives.com
- **Information department:** Bison QESH
- **Emergency telephone number:** +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard-determining components of labeling:**  
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)
- **Hazard statements**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.
- **Precautionary statements**  
P261 Avoid breathing vapours.  
P280 Wear protective gloves / eye protection.

(Contd. on page 2)

US-US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 1)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 1  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2  
FIRE 1 Fire = 1  
REACTIVITY 0 Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture of the substances listed below with nonhazardous additions.  
Adhesive

· **Dangerous components:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	10-25%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1-2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.

(Contd. on page 3)

US-US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Send for recovery or disposal in suitable receptacles.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	90 mg/m <sup>3</sup>
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m <sup>3</sup>

· **PAC-2:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	990 mg/m <sup>3</sup>
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m <sup>3</sup>

· **PAC-3:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	5,900 mg/m <sup>3</sup>
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m <sup>3</sup>

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

(Contd. on page 4)

US-US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 3)

- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 10
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Recommended filter device for short term use:** Combination filter A-P1
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
Recommended thickness of the material: > 0,12 mm  
Nitrile rubber, NBR
- **Penetration time of glove material**  
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
- **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

US-US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 4)

- Goggles recommended during refilling.
- **Body protection:** Use protective suit.

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** Undetermined.

· **Flash point:** >150 °C (>302 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

- **Lower:** Not determined.
- **Upper:** Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 2.5 g/cm<sup>3</sup> (20.863 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

- **Dynamic:** Not determined.
- **Kinematic:** Not determined.

· **Solvent content:**

· **VOC content:** 0.00 %

· **Solids content:** 74.0 %

(Contd. on page 6)

US-US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 5)

· **Other information**

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with amines.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Danger of toxic pyrolysis products.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)

US-US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.
- **Uncleaned packagings:**
- **Recommendation:**  
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

\* **14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, ADN</b>	not regulated
· <b>ADR/ADN, IMDG, IATA</b>	not regulated
	-
· <b>UN proper shipping name</b>	
· <b>DOT, ADR/ADN, ADN, IMDG, IATA</b>	not regulated
· <b>Transport hazard class(es)</b>	
· <b>DOT, ADR/ADN, ADN, IMDG, IATA</b>	
· <b>Class</b>	not regulated
· <b>Packing group</b>	
· <b>DOT, ADR/ADN, IMDG, IATA</b>	not regulated
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
· <b>IMDG</b>	
· <b>Remarks:</b>	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III.

(Contd. on page 8)

US-US

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 7)

- |                                 |  |
|---------------------------------|--|
| ·                               | See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2 |
| · <b>UN "Model Regulation":</b> | not regulated                                    |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )
------------	---

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
------------	--

1317-65-3	calcium carbonate
-----------	-------------------

90-72-2	2,4,6-tris(dimethylaminomethyl)phenol
---------	---------------------------------------

16389-88-1	dolomite
------------	----------

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
------------	---	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

US-US



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2019

Reviewed on 05/23/2019

**Trade name:** GRIFFON EPOXY REPAIR STICK 114G\*12 L41

(Contd. of page 8)

**Hazard pictograms**

GHS07

**Signal word** Warning**Hazard-determining components of labeling:**reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)**Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

**Precautionary statements**

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** Bison QESH**Contact:** Reach coordinator**Date of preparation / last revision** 05/23/2019 / 96**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

**\* Data compared to the previous version altered.**

US-US