

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

1 Identification

- **Product identifier**
- **Trade name:** GRIFFON WHITE GREASE AER 300ML*12 L222
- **Application of the substance / the mixture** Lubricant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com
- **Information department:** Bison QESH
- **Emergency telephone number:** +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy

- **Hazard statements**

H222 Extremely flammable aerosol.

(Contd. on page 2)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0

FIRE 4 Fire = 4

REACTIVITY 3 Reactivity = 3

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Lubricant

· **Dangerous components:**

64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-50%
106-97-8	butane	25-50%
74-98-6	propane	10-25%
75-28-5	isobutane	1-2.5%

4 First-aid measures

· **Description of first aid measures**

· **General information:** No special measures required.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

No special measures required.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
106-97-8	butane	5500* ppm
74-98-6	propane	5500* ppm
75-28-5	isobutane	5500* ppm

· **PAC-2:**

64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
106-97-8	butane	17000** ppm
74-98-6	propane	17000** ppm
75-28-5	isobutane	17000** ppm

· **PAC-3:**

64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
106-97-8	butane	53000*** ppm
74-98-6	propane	33000*** ppm

(Contd. on page 4)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

75-28-5 isobutane	(Contd. of page 3) 53000*** ppm
-------------------	------------------------------------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 2 B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

106-97-8 butane

REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)

74-98-6 propane

PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; D, EX

75-28-5 isobutane

TLV	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

(Contd. on page 5)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 4)

- **Breathing equipment:** Not required.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
- **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
- **Eye protection:** Not required.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol
 Color: According to product specification

· **Odor:** Characteristic
· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 180 °C (356 °F)

· **Flash point:** -97 °C (-142.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 0.6 Vol %
 Upper: 10.9 Vol %

· **Vapor pressure at 20 °C (68 °F):** 8300 hPa (6225.5 mm Hg)

· **Density at 20 °C (68 °F):** 0.68 g/cm³ (5.675 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not applicable.

(Contd. on page 6)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 5)

· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	39.5 %
VOC content:	41.28 %
Solids content:	0.0 %
· Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

106-97-8 butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)

US-US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 6)

· Carcinogenic categories**· IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity**· Aquatic toxicity:** No further relevant information available.**· Persistence and degradability** No further relevant information available.**· Behavior in environmental systems:****· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment**· PBT:** Not applicable.**· vPvB:** Not applicable.**· Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods**· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packagings:**· Recommendation:**

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· UN-Number**· DOT, ADR/ADN, IMDG, IATA**

UN1950

· UN proper shipping name**· DOT**

Aerosols, flammable

· ADR/ADN

1950 AEROSOLS

(Contd. on page 8)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 7)

· **IMDG** AEROSOLS
· **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1
· **Label** 2.1

· **ADR/ADN**



· **Class** 2.5F Gases
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1

· **Packing group**
· **DOT, ADR/ADN, IMDG, IATA** not regulated

· **Environmental hazards:**
· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases
· **Danger code (Kemler):** -
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.

· **Segregation Code** SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

(Contd. on page 9)

US-US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 8)

<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations 	<p>On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg</p>
<ul style="list-style-type: none"> · ADR/ADN · Excepted quantities (EQ) 	<p>Code: E0 Not permitted as Excepted Quantity</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks: 	<p>1L Code: E0 Not permitted as Excepted Quantity Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1950 AEROSOLS, 2.1</p>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

64742-48-9	Naphtha (petroleum), hydrotreated heavy
106-97-8	butane
74-98-6	propane
75-28-5	isobutane

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 10)

US-US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 9)

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories**EPA (Environmental Protection Agency)**

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy

Hazard statements

H222 Extremely flammable aerosol.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Bison QESH**Contact:** Reach coordinator**Date of preparation / last revision** 05/24/2019 / 17**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)

US-US



Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2019

Reviewed on 05/24/2019

Trade name: GRIFFON WHITE GREASE AER 300ML*12 L222

(Contd. of page 10)

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

· * **Data compared to the previous version altered.**

US-US