



# ALU ZINCSPRAY

## ALUMINIUM COLOURED, FAST DRYING ZINC COATING.



### TECHNICAL PROPERTIES

**Temperature resistance:** -30°C - +120°C

### TECHNICAL SPECIFICATIONS

**Chemical base:** Zinc/Alu powder in solvent mixture

**Colour:** Aluminium

**Specifications:** Recoatable: immediately after it becomes matte.

### STORAGE CONDITIONS

At least 24 months after date of manufacture. Close the container properly and store in a dry, cool and frost-free location.

### PRODUCT DESCRIPTION

Aluminium coloured, fast drying zinc coating.

### FIELD OF APPLICATION

For protecting (cold galvanizing) of metal against rust and corrosion, such as bodywork, welding seams, fences, gutter brackets and stairs. Also to repair damage to previously galvanised metal.

### PROPERTIES

- Rust and corrosion resistant
- Aluminium coloured
- Quick-drying
- Electrically conductive
- Resistant to temperatures between -30°C to +120°C
- Contains 98% pure zinc
- Paintable

### PREPARATION

**Preliminary surface treatment:** Make sure that the surface is clean, dry, and free of grease. Remove rust, mill scale and loose coatings.

### APPLICATION

#### Directions for use:

Shake well before use. Spray surface evenly and thinly from a distance of approx. 30 cm. It is better to apply several thin coatings than one thick coating. Apply the next layer within 10 minutes or 24 hours after the previous layer. Regularly shake during use. After use, hold the can upside down and spray until only propellant gas is released.

**Stains/residue:** Remove wet stains with thinner. Remove dry stains with paint stripper.