



# GLASS-TIC ALU

**SELF-ADHESIVE SEALING TAPE BASED ON PETROLATUM WITH ALUMINIUM SURFACE LAYER**



## PRODUCT DESCRIPTION

Self-adhesive sealing tape based on petrolatum with aluminium surface layer.

## FIELD OF APPLICATION

Suitable for sealing, protection and repair of, among others, T-irons, glass roofs, glasshouses and skylights. Adheres to nearly all substrates like, for instance, glass, stone, concrete, lead, zinc, aluminium, wood and various synthetics. Highly flexible, extremely suitable for uneven surfaces and/or forms. Suitable for indoor and outdoor applications.

## PROPERTIES

- Resistant to all types of weather
- Paintable

## PREPARATION

**Working Conditions:** Do not use at temperatures  $\leq +5^{\circ}\text{C}$ .

**Preliminary Surface Treatment:** Surfaces must be dry, clean, and free of dust and grease. Remove loose paint traces and rust.

## APPLICATION

### Directions for use:

Remove the liner and apply without pressure. Tool the entire length starting from the middle using a cloth or roller and press hard. If surfaces are at an angle with each other, then press hard in the corner.

## TECHNICAL SPECIFICATIONS

Chemical base:	Fabric carrier impregnated with petrolatum sealing mass
Colour:	Aluminium
Material top layer:	Aluminium
Minimum temperature resistance:	$-40^{\circ}\text{C}$
Maximum temperature resistance:	$65^{\circ}\text{C}$
Moisture resistance:	Very good
Thickness (mm):	1.2 mm
Thickness top layer:	0,04
UV resistance:	Good
Water resistance:	Very good

## STORAGE CONDITIONS

Shelf life: At least 24 months after production.

Store in well-sealed packaging at temperatures between  $+5^{\circ}\text{C}$  and  $+25^{\circ}\text{C}$ . Close the container properly and store in a dry, cool and frost-free location.

Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.