



# RAPID CEMENT

## CEMENT FOR REPAIRS TO MASONRY AND CONCRETE.



### TECHNICAL SPECIFICATIONS

Colour:	Grey
pH-value approx.:	12
Water resistance:	Very good

### STORAGE CONDITIONS

Minimum 12 months.

Store in properly sealed packaging in a dry place at between +5°C and +25°C.

### PRODUCT DESCRIPTION

Fast curing cement for repairs to masonry and concrete.

### FIELD OF APPLICATION

Suitable for repairs to masonry and concrete. Suitable for, e.g., mounting work, fixing bolts, hooks and screws, repairing leaks in masonry and concrete.

### PROPERTIES

· Very fast

### PREPARATION

**Working Conditions:** Use only at temperatures between +5°C and +25°C.

**Personal safety:** Wear gloves and safety goggles.

**Surface Requirements:** The substrate must be solid, clean and free of grease. Remove loose parts.

**Preliminary Surface Treatment:** Slightly moisten dry surfaces.

**Tools:** Float, trowel, putty knife.

### APPLICATION

#### Directions for use:

Mix 3 parts rapid cement with 1 part of water to form a solid homogeneous paste. Apply paste immediately (within one minute) with a float, trowel or putty knife. Properly close the container immediately after use.

**Stains/residue:** Remove wet rapid cement residue immediately with water. Cured rapid cement residue can only be removed mechanically.

**Points of attention:** At low temperatures, the curing can be accelerated by using warm or hot water. For larger repairs make a mixture of GRIFFON rapid cement, water and fine sand.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.