



LUBRICANT

LUBRICANT FOR PIPE SYSTEMS WITH RUBBER SLEEVE CONNECTIONS



PRODUCT DESCRIPTION

Lubricant for pipe systems with rubber sleeve connections.

FIELD OF APPLICATION

For assembling pipes, sleeves and fittings with rubber sleeve (sliding socket) connections in drain systems. Suitable for all diameters. Suitable for PVC-U, ABS, PE, PP, GRP, concrete and coated cast iron.

PROPERTIES

- Re-adjustable
- Acid-free
- Thixotropic

PREPARATION

Working Conditions: Do not use in temperatures $\leq +0^{\circ}\text{C}$.

APPLICATION

Directions for use:

1. Cut pipes square, remove burrs and chamfer. 2. Remove dirt and moisture. 3. Apply slipping agent to pipe end and rubber sleeve. 4. Join parts immediately by sliding the tube into the sliding socket until the stopper. 5. Properly close the container immediately after use.

Stains/residue: Remove residues with a degreaser.

TECHNICAL SPECIFICATIONS

Chemical base:	Silicone oil
Colour:	Transparent

STORAGE CONDITIONS

Shelf life: At least 36 months after production.

Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.