



# M-385

## LIQUID, TRANSPARENT, CONTACT ADHESIVE FOR BONDING PVC FOIL



### TECHNICAL SPECIFICATIONS

Chemical base:	TPU in solvent blend
Colour:	Transparent
Density approx.:	0,88 g/cm <sup>3</sup>
Solid matter approx.:	22 %
Viscosity approx.:	3300 mPa·s

### STORAGE CONDITIONS

Shelf life: At least 24 months after production.

Stored in unopened packaging between +5°C and +25°C.

Best Before Date (MM/YY): see packaging. Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

### PRODUCT DESCRIPTION

Liquid, transparent, contact adhesive for bonding PVC foil.

### FIELD OF APPLICATION

For mutually bonding PVC foils as well as for bonding PVC foil to hard PVC, rubber, canvas and wood such as for swimming pools, basins, ponds and roofs.

### PROPERTIES

- High level of initial bonding
- Waterproof
- Plasticiser Resistant
- Permanently flexible
- With brush
- With quick release cap

### PREPARATION

**Working Conditions:** Do not use in temperatures  $\leq +10^{\circ}\text{C}$ .

### APPLICATION

#### Directions for use:

1. Clean the surfaces to be bonded with Griffon Cleaner. 2. Apply adhesive thinly and evenly to both bonding surfaces and allow to dry for 10 to 25 minutes. 3. Join surfaces and press firmly. Remove excess adhesive. Properly close the container immediately after use.

**Stains/residue:** Remove adhesive stains with Griffon Cleaner and Cleaner Cloth.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.