



# NO-SPAT®

## NON-FLAMMABLE, SILICONE-FREE WELDING SPRAY



### PRODUCT DESCRIPTION

Non-flammable, silicone-free welding spray.

### FIELD OF APPLICATION

For preventing adhesion of weld spatter on gun parts, clamps, brackets, burners, nozzles and equipment in MIG, MAG and CO2 welding.

### PROPERTIES

- Non-flammable
- Silicone-free

### APPLICATION

#### Directions for use:

Shake well before use.

Spray welding torch, nozzle and object thinly and evenly from a short distance (approx. 20-30 cm). After welding, the weld spatter can be easily removed from the workpiece. Residues are easily removed with a degreaser.

**Points of attention:** Do not spray during welding. Do not spray on painted, varnished or synthetic surfaces. Keep aerosol out of reach of the welding spatters.

### TECHNICAL SPECIFICATIONS

Chemical base:	Oil in methylene chloride
Colour:	Cream

### STORAGE CONDITIONS

A minimum of 36 months.

Close the container properly and store in a dry, cool and frost-free location.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.