



GEOTEXTILE

ELASTIC NON WOVEN CLOTH FOR WATERPROOFING AND AIRTIGHT CONSTRUCTION



APPLICATION

Directions for use:

Before using HBS-200® Liquid Rubber or SMP-300® Polymer coating, stir manually until a homogenous colour is obtained. It is not recommended to use an electric mixer with a high rotational speed for stirring. For seam, crack and tear-bridging applications, GRIFFON GeoTextile should be used. GRIFFON GeoTextile must be applied in still wet HBS-200® Liquid Rubber or SMP-300® Polymer coating. Then immediately level off with a second layer. Always ensure a layer thickness of at least 2 mm after curing.

PRODUCT DESCRIPTION

Elastic cloth for use in combination with HBS-200® and SMP-300® coatings.

FIELD OF APPLICATION

Suitable for use in combination with HBS-200® Liquid Rubber and SMP-300® Polymer coating in case of seam, crack and tear-bridging applications. Suitable for sealing and protecting a wide variety of materials, such as concrete, metal, stone, wood, bitumen, zinc, PVC, EPDM (test first), etc. For floors, partitions, walls, seams, joints, conduits and structural components. Excellent for both interior and exterior applications (bathrooms, cellars, balconies, roofs, etc.) including gutters, shower basins, conduit ducts, floor seams, expansion joints, window frame joints and ground level items. Also suitable as a waterproof layer under tiles in damp environments, such as bathrooms, swimming pools, balconies, terraces, etc.

PROPERTIES

- Elastic
- Excellent absorption of HBS-200® Liquid Rubber and SMP-300® coatings.
- Strong
- Non-woven

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.