



SILICONE GREASE

LUBRICANT ON A 100% SILICONE BASE



TECHNICAL SPECIFICATIONS

Chemical base:	100% pure silicones
Colour:	White (Transparent)
Density approx.:	1 g/cm ³
Minimum temperature resistance:	-60 °C
Maximum temperature resistance:	200 °C
Viscosity:	Pasty

STORAGE CONDITIONS

Shelf life: At least 36 months after production.
 Stored in unopened packaging between +5°C and +25°C.
 Close packaging properly after use and store in a dry, cool, and frost-free location.
 Limited shelf life after opening.

PRODUCT DESCRIPTION

Lubricant for hydrants and valves on a 100% silicone base.

FIELD OF APPLICATION

For or metals and synthetics. Also suitable for lubricating hinges, (sliding) doors, windows, drawers, rails and roller bearings and for maintaining motorcycles, bicycles, scooters, machinery, (garden) tools and sports equipment. Prevents (door) rubbers from freezing

PROPERTIES

- High chemical resistance
- Not soluble in water
- Rust and corrosion resistant
- Water repellant
- Water resistant
- Electrically insulative

CERTIFICATES & STANDARDS

Certificates

ACS

ACS: In accordance with the positive lists of ACS (Attestation de Conformité Sanitaire).
 Certificate Eurofins 22 CLP NY 034.

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

APPLICATION

Directions for use:

Coat surface thinly and evenly.

Points of attention: Treated surfaces are not paintable.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.