#### 1233451 - GRIFFON LUBRIT-ALL® AEROSOL 300 ML NL/FR/DE



# **UBRIT-ALL**® MULTIFUNCTIONAL MAINTENANCE AGENT



## **PRODUCT DESCRIPTION**

Multifunctional maintenance agent for lubricating, protecting, cleaning and loosening in 1001 applications.

# FIELD OF APPLICATION

For lubricating, protecting, cleaning and loosening in 1001 applications, such as in the home, workshop, garage, garden, caravan, car and boat. Suitable for, e.g., lubricating sliding doors, windows, hinges, latches, locks and roller bearings. Also for maintenance of (motor) bikes, scooters, machinery, (garden) tools and sports equipment. Also for removing dirt and grease from wheel rims, (bicycle) chains, gears, bearings and loosening rusted and oxidised (fixation) materials such as bolts and nuts.

# PROPERTIES

- Lubricates
- · Protects
- Removes dirt and grease
- Unlatches
- · Corrosion retardant
- · Dissolves dirt and oxides
- · Moisture repellent
- · Silicone-free
- · With extra precision spray hose
- · Can be used in all positions

#### PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

# **APPLICATION**

**Directions for use:** 

Shake well before use.

Spray surface(s) evenly from a distance of approx. 10-20 cm. For use as penetrating oil, spray surface(s) generously. After about 5 -10 minutes, the parts can be disassembled. For preventive use parts must be treated first, then assembled. Stains/residue: Remove stains with Griffon Primor or degreaser. Points of attention: Use the additional spray hose integrated in the cap for optimum dosage.

## **TECHNICAL SPECIFICATIONS**

Chemical base:	Solvents and mineral oil
Colour:	Transparent
Minimum temperature resistance:	-50 °C
Maximum temperature resistance:	125 °C

## **STORAGE CONDITIONS**

Shelf life: At least 36 months after production. Stored in unopened packaging between +5°C and +25°C. Close packaging properly after use and store in a dry, cool, and frost-free location. Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.

20240906