GAS LEAK DETECTOR

FOR DETECTING LEAKS IN GAS AND COMPRESSED AIR PIPING

PRODUCT DESCRIPTION
For detecting leaks in gas and compressed air piping.

FIELD OF APPLICATION
For the detection of leaks, e.g., in piping, fittings, valves and taps in gas and compressed air systems, refrigeration and airconditioning systems, pressure vessels, tanks, furnaces, burners, gas cylinders and compressors. Suitable for all (combustible) types of gases (including oxygen and freon).

PROPERTIES
· Non-corrosive
· Non-flammable
· Non-toxic
· Can be used in all positions

CERTIFICATES & STANDARDS

Certificates	
DIN DVGW CERT	DVGW: Leak detector spray. Certificate NG-5170AO0659

PREPARATION
Working Conditions: Do not apply at temperatures below 0°C.

APPLICATION
Directions for use:
Shake well before use.
Pressurise the system to check and inject from a distance of about 30-50 cm. In case of leaks, bubbles will develop. For very small leaks this may take some time.
Stains/residue: Remove stains with water.

TECHNICAL SPECIFICATIONS

Chemical base:	Acid-free soap solution
Colour:	Transparent

STORAGE CONDITIONS
Shelf life: At least 36 months after production.
Stored in unopened packaging between +5°C and +25°C.
Close packaging properly after use and store in a dry, cool, and frost-free location.
Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.