

**F-40****FIXATION AGENT FOR FIXING POLYPROPYLENE (PP) PIPES AND FITTINGS****STORAGE CONDITIONS**

Shelf life: At least 12 months after production.

Stored in unopened packaging between +5°C and +25°C.

Best Before Date (MM/YY): see packaging. Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

PRODUCT DESCRIPTION

Fixation agent for fixing polypropylene (PP) pipes and fittings.

FIELD OF APPLICATION

For fixing polypropylene (PP) pipes and fittings with rubber sleeve (sliding socket) connections in drain systems. Especially to prevent the drifting apart of pre-fab systems and folding of corners, for example, during transport.

PROPERTIES

- Thixotropic
- Black

PREPARATION**Working Conditions:** Do not use in temperatures $\leq +5^{\circ}\text{C}$.**APPLICATION****Directions for use:**

1. Cut pipes square, remove burrs and chamfer. 2. Clean surfaces. 3. Stir well before use. 3. Apply fixation agent to pipe end and rubber sleeve. 4. Join parts immediately by sliding the tube into the sliding socket until the stopper. Properly close the container immediately after use.

Stains/residue: Remove adhesive stains with Griffon Cleaner and Cleaner Cloth.**TECHNICAL SPECIFICATIONS**

Colour:	Black
Density approx.:	1,5 g/cm ³
Solid matter approx.:	70 %
Viscosity approx.:	1800 mPa·s

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.