



PTFE SPRAY

HIGH-QUALITY MULTI-FUNCTIONAL LUBRICANT BASED ON P.T.F.E.



TECHNICAL SPECIFICATIONS

Chemical base:	Mineral oil with P.T.F.E.
Colour:	Transparent
Minimum temperature resistance:	-50 °C
Maximum temperature resistance:	200 °C
Viscosity:	Liquid

STORAGE CONDITIONS

Shelf life: At least 36 months after production.

Stored in unopened packaging between +5°C and +25°C.

Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

PRODUCT DESCRIPTION

High-quality multi-functional lubricant based on P.T.F.E.

FIELD OF APPLICATION

For the lubrication of metals and synthetics that are submitted to heavy and prolonged loads, such as machines, hinges, tools, chains, derailleur gears, roller bearings and pulleys. For use in workshop, house, garage, caravan, car and boat, among others.

PROPERTIES

- Silicone-free
- Moisture resistant
- Does not affect synthetics and rubbers
- With extra precision spray hose
- Can be used in all positions

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

APPLICATION

Directions for use:

Shake well before use.

Spray surface(s) evenly from a distance of approx. 10-20 cm.

Stains/residue: Remove stains with Griffon Primor or degreaser.

Points of attention: Use the additional spray hose integrated in the cap for optimum dosage.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.