



MULTI-TOOL

MULTIPURPOSE TOOL



PRODUCT DESCRIPTION

For opening cartridges, cutting nozzles and applying and/or removing sealants.

FIELD OF APPLICATION

Suitable for use with all sealants such as Silicone Sealants (S-100 and S-200), Acrylic Sealants (A-100) and Poly Max®.

PROPERTIES

- Multi-functional
- Simple to use
- Ergonomic

APPLICATION

Directions for use:

1. Opening cartridges/cutting nozzles: Place the Multi-Tool on the nipple of the cartridge and cut open the cartridge. Place the nozzle at an angle against the blade and cut at the desired joint width. 2. Applying sealants: Moisten the Multi-Tool and the applied sealant seam with GRIFFON Silicone Finish. Place it with the convex side against the sealant seam and wipe in a single movement along the seam to level it and remove any excess sealant. 3. Removing cured sealants: Pull the cured sealant seam apart using the hook. Use GRIFFON Silicone Remover to remove any remaining sealant residue.

Stains/residue: Remove non-cured sealant residue from the Multi-Tool immediately after use.

TECHNICAL SPECIFICATIONS

Colour:	Black
---------	-------

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.