



UNILUBE

TRANSPARENT LUBRICANT FOR CLEAN AND LIGHT LUBRICATION



TECHNICAL SPECIFICATIONS

| | |
|---------------------------------|------------------------|
| Chemical base: | Mineral oil |
| Colour: | Transparent |
| Density approx.: | 0.86 g/cm ³ |
| Minimum temperature resistance: | -40 °C |
| Maximum temperature resistance: | 125 °C |
| Viscosity: | Liquid |

STORAGE CONDITIONS

A minimum of 24 months.
Close the container properly and store in a dry, cool and frost-free location.

PRODUCT DESCRIPTION

Transparent lubricant for clean and light lubrication.

FIELD OF APPLICATION

For clean and light lubrication of rotating metal parts such as (sewing) machines, sliding doors, locks, hinges, (curtain) rails, roller bearings and household appliances.

PROPERTIES

- FDA-approved
- Acid-free
- Transparent
- Silicone-free
- Convenient dosage bottle

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

APPLICATION

Directions for use:

Treat surface thinly and evenly.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.