



# MEET THE POLY MAX<sup>®</sup> FAMILY



**HIGH TACK**  
Bonding & Fixing  
Very high initial  
bond strength



**PRO POWER**  
Bonding & Fixing  
Very high final  
bond strength



**FIX & SEAL**  
Bonding, Fixing & Sealing  
Ideal for fixing in  
combination with sealing



**SEALANT**  
100% Sealing  
Premium, multifunctional  
sealant

# MEET THE POLY MAX® FAMILY



## POLY MAX® HIGH TACK EXPRESS

Solvent-free assembly adhesive based on SMP-Polymer with **very high initial bond strength** and very fast strength build-up: its final strength is attained after only 4 hrs. and both colours can be handled after approx. 30 min. Shoring or clamping is usually not necessary. Excellent for heavy materials, vertical applications and overhead applications.



## POLY MAX® PRO POWER EXPRESS

Solvent-free assembly adhesive with **very high final strength** and very fast strength build-up, based on SMP-Polymer. Final strength is attained after only 4 hrs. The white variant can be handled after approx. 30 min. and the crystal clear variant after approx. 2 hrs. Ideal for bonding insulation materials and skirting boards for example. Suitable for many building materials and substrates.



Excl. Crystal Clear



## POLY MAX® FIX & SEAL EXPRESS

Solvent-free assembly adhesive and sealant based on SMP-Polymer with high elasticity and very fast strength build-up. After only 4 hrs. the final strength is reached. Suitable for virtually all materials and substrates.

**Ideal for a combination of fixing and sealing.**

EN 15651-1/3: F-EXT-INT/S.



Excl. Crystal Clear



## POLY MAX® SEALANT ALL JOINTS

Premium quality, solvent-free, easy to use multifunctional sealant with very high elasticity (100% modulus: 0.6 Mpa) **for sealing applications in sanitary, interior and exterior areas.** Good mildew resistance. EN 15651-1/3: F-EXT-INT/S.

