1233406 - GRIFFON SILICONE SPRAY AEROSOL 300 ML NL/FR/DE



SILICONE SPRAY UNIVERSAL TRANSPARENT SLIPPING, LUBRICATING AND ANTI-ADHESION AGENT



APPLICATION

Directions for use:

Shake well before use.

Spray surface(s) evenly from a distance of approx. 10-20 cm. **Points of attention:** Use the additional spray hose integrated in the cap for optimum dosage. Do not use on silicon compounds such as glass and stone. Treated surfaces are not paintable.

TECHNICAL SPECIFICATIONS

Chemical base:	Coloured oil in solvent
Colour:	Transparent
Minimum temperature resistance:	-50 °C
Maximum temperature resistance:	200 °C

STORAGE CONDITIONS

Shelf life: At least 36 months after production. Stored in unopened packaging between +5°C and +25°C. Close packaging properly after use and store in a dry, cool, and frost-free location. Limited shelf life after opening.

Limited shelf life after open

PRODUCT DESCRIPTION

Universal transparent slipping, lubricating and anti-adhesion agent based on pure silicone oil.

FIELD OF APPLICATION

For clean and light lubrication of sliding doors, sliding windows, drawers and bay windows, locks, wiring, cables, hinges, latches, zips, (curtain) rails, roller bearings, wheels and levelling feet, among others. Also for maintenance of (motor) bikes, scooters, machinery, (garden) tools and sports equipment. Prevents dirt and grease deposits on biological waste bins, exhaust hoods, fans, ovens, microwaves, bumpers and grills. Makes cleaned textiles and leather water repellent, prevents freezing of (door) rubbers and keeps chains and gears clean.

PROPERTIES

- · Rust and corrosion resistant
- · Water displacing
- · Water repellant
- · Electrically insulative
- · Chemical resistant
- \cdot Low surface tension
- · With extra precision spray hose
- \cdot Can be used in all positions

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.

