



# LUBRICANT

## LUBRICANT FOR PIPE SYSTEMS WITH RUBBER SLEEVE CONNECTIONS



### TECHNICAL SPECIFICATIONS

Acid free:	Yes
Chemical base:	Acid-free vaseline
Colour:	White
Density approx.:	0.81 g/cm <sup>3</sup>
Minimum temperature resistance:	-20 °C
Maximum temperature resistance:	45 °C
Viscosity:	Pasty

### STORAGE CONDITIONS

Stored in unopened packaging between +5°C and +25°C.  
Best Before Date (MM/YY): see packaging. Close packaging properly after use and store in a dry, cool, and frost-free location.

### PRODUCT DESCRIPTION

Lubricant for pipe systems with rubber sleeve connections.

### FIELD OF APPLICATION

For assembling pipes, sleeves and fittings with rubber sleeve (sliding socket) connections in drain systems. Suitable for all diameters. Suitable for PVC-U, ABS, PE, PP, GRP, concrete and coated cast iron.

### PROPERTIES

- Re-adjustable
- Acid-free
- Thixotropic

### PREPARATION

**Working Conditions:** Do not use in temperatures  $\leq +0^{\circ}\text{C}$ .

### APPLICATION

**Coverage:** Indication of the number of joints per 1 L:

Ø	32	40	50	75	90	110	160	250
#	900	600	400	200	135	90	45	20

### Directions for use:

1. Cut pipes square, remove burrs and chamfer. 2. Remove dirt and moisture. 3. Apply slipping agent to pipe end and rubber sleeve. 4. Join parts immediately by sliding the tube into the sliding socket until the stopper. 5. Properly close the container immediately after use.

**Stains/residue:** Remove residues with a degreaser.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.