



SEALANT REMOVER

FAST & EASY SOLUTION FOR REMOVING CURED SEALANT RESIDUES



TECHNICAL SPECIFICATIONS

Density approx.:	0,84 g/cm ³
Viscosity:	Gel

STORAGE CONDITIONS

Shelf life: At least 24 months after production.

Store in properly sealed packaging in a dry place at between +5°C and +25°C.

Limited shelf life after opening.

PRODUCT DESCRIPTION

Fast & easy removing paste for cured sealant residues.

FIELD OF APPLICATION

Suitable for cured silicone and polymer sealant residues.

Suitable for ceramic tiles, glass, metal, synthetics, laminated material, aluminum and enamel.

Not suitable for nylon.

PREPARATION

Working Conditions: Only apply at temperatures between +5°C and +40°C.

Tools: GRIFFON Multitool, Sharp box cutter or Glass Scraper, Cleaning Cloth, Sanitary Sponge

APPLICATION

Directions for use:

Shake closed bottle vigorously for about a minute. Cut old sealant loose with a sharp box cutter/ knife. Use the hook of the GRIFFON Multitool to pull the old sealant out of the joint. Remove as much of the existing sealant as possible. Apply the paste generously onto the old sealant residue. Allow to act for at least 30 minutes. Remove old sealant residues with cleaning cloth, glass scraper or sanitary sponge. If necessary, repeat the treatment. Clean the joint thoroughly with a sponge and water. Degrease the surface with a lint-free cloth and let it dry thoroughly. Afterwards it's ready for a new sealant application.

Advice: Test the remover on a non-visible spot as staining may occur on sensitive materials.

Points of attention: May cause staining on porous materials and painted surfaces.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.