



LEAKSEALER

SUPER CONCENTRATE FOR SEALING LEAKS IN CENTRAL HEATING SYSTEMS



PRODUCT DESCRIPTION

Super concentrate for sealing leaks in central heating systems.

FIELD OF APPLICATION

For sealing leaks (up to \varnothing 1 mm) in central heating systems. Not for preventive use. Also suitable for combination boilers and underfloor heating.

PROPERTIES

- Super concentrated
- With special injector

PREPARATION

Tools: Sealant gun, radiator key, Allen key

APPLICATION

Coverage: One cartridge per 100 litres of installation content.

Directions for use:

Cutting the nozzle of the injector supplied to the correct diameter and screw it to the venting valve of the radiator. Cut the cone-shaped head at the top of the cartridge down to the screw thread with a sharp knife. Screw the blue cap of the injector as far as possible on the thread of the cartridge and insert the cartridge into a sealant gun.

1. Turn the system off and let it cool. 2. Isolate a radiator from the rest of the installation by closing the radiator valve and foot control valve. If this is not possible, the product can also be added via the filling hose. 3. Remove the venting pin. 4. Cut the injector to the correct diameter and screw it into the thread of the breather. 5. Remove the foil, screw the cap on the cartridge and place it in a sealant gun. 6. Mount the injector on the cap. 7. Open the radiator valve or foot control valve, inject the entire contents and close the valve. 8. Release the pressure from the radiator by pressing the pin on the caulking gun. 9. Remove the injector from the radiator. 10. Mount the venting pin and turn the radiator valve and foot control valve open. 11. Turn the system on and let it run. Ensure that the entire system is open. Depending on the place and nature of the leakage sealing will take 30 minutes to several hours.

Points of attention: Easy to use, because the system can remain in normal operation during use. Keep a cloth or bucket at hand to catch the water that escapes by the overpressure when removing the venting pin. Simple and easy to add via the radiator or the installation's fill valve. Does not attack metal (including aluminium), synthetics and other materials. Compatible with all other Griffon Central heating Water treatment products. A cartridge is sufficient to protect a heating system of moderate size (up to 10 radiators = about 100 liters). Overdose is not a problem.

TECHNICAL SPECIFICATIONS

Colour:	White
Density approx.:	1.02 g/cm ³
Viscosity:	Liquid

STORAGE CONDITIONS

Shelf life: At least 36 months after production.

Stored in unopened packaging between +5°C and +25°C.

Best Before Date (MM/YY): see packaging. Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.