



POOL LEAK SEALER - PROFESSIONAL POOL QUALITY

LIQUID SEALER FOR CONCRETE POOLS



PRODUCT DESCRIPTION

Pool Leak Sealer is an easy-to-use liquid sealer designed for repairing leaks in swimming pools without the need to remove water. Utilizing advanced Crystallization Technology, it forms a hard, durable seal in the presence of carbon dioxide without altering the pool's appearance.

FIELD OF APPLICATION

Suitable for concrete and segment pools only.

PROPERTIES

- Very easy to use
- Can seal cracks up to 4 -5 mm or 10 - 50 cm water loss/24 hrs (50M3)
- No need to remove pool water
- Does not change appearance
- Durable permanent seals due to advanced Crystallization technology
- 5 years shelf life

PREPARATION

Preliminary Surface Treatment: Determine whether the leak is in the pipes, overflow, or the pool itself.

Tools: Submersible pump

APPLICATION

Coverage: Mixing Ratio: 1:1.000 = 1 liter Leak Sealer to 1.000 liters of swimming pool water.

Directions for use:

Turn off the pool's circulation pump and filter. Thoroughly shake the jerrycan to ensure the fibers are well mixed.

1. Add the appropriate amount of Leak Sealer to the pool, using a mixing ratio of 1 liter of Leak Sealer to 1.000 liters of pool water. Ensure all fibers from the canister are added to the pool. If fibers remain in the canister, fill it halfway with pool water and shake again before pouring into the pool. 2. Create circulation without the use of filtration by placing a submersible pump in the pool and run this circulation for 1 to 3 days until the leak is sealed. 3. Maintain the water in the pool and filter out the fibers. Adjust the pH level of the pool water if necessary, using pH-minus, or drain the pool to clean any remaining product residues from surfaces and tiles.

Stains/residue: Immediately rinse off any spilled product from surfaces outside the pool with water to prevent staining which cannot be removed.

Advice: Do not use if the water hardness exceeds 25° DH (German hardness). Pools may develop new leaks if affected by seismic activity or foundation movements.

Points of attention: Pool Leak Sealer is only effective on hard-walled concrete or segment pools. Immediately rinse off any spilled product from surfaces outside the pool with water to prevent staining, which cannot be removed.

TECHNICAL SPECIFICATIONS

Consistency:	Liquid
Density approx.:	1,35 g/cm ³
pH-value approx.:	11

PACK SIZES

Jerry Can 10 Liter

STORAGE CONDITIONS

Store in a dry, frost-free place between +5°C and +25°C. The shelf life is 5 years. Best Before Date (MM/YY).

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.