

# POLY MAX<sup>®</sup> SEALANT ALL JOINTS THE CHOICE OF THE PRO

Premium sealant for interior, sanitary & exterior



Griffon. The choice of the pro.

SEL LI

Ř



### THE CHOICE OF THE PRO FOR ALL SEALING JOBS

Girffon proudly presents Poly Max<sup>®</sup> Sealant All Joints, the next generation of our esteemed Poly Max<sup>®</sup> family. Leveraging 20 years of innovation, Poly Max<sup>®</sup> Sealant All Joints is designed to deliver superior performance for all your needs: sealing, filling and finishing. This premium, multifunctional sealant is easy to use, fast curing and for all kinds of sealing projects in interior, sanitary and exterior areas.

Our new all-in-one sealant replaces silicone, acrylic, and PU sealants, retaining all the benefits but without the disadvantages. Its unique formula ensures no shrinkage, unmatched flexibility, and resistance to mildew and UV rays, making it ideal for professionals who demand reliability and efficiency.

Available in six colors, including transparent, Poly Max<sup>®</sup> Sealant All Joints is your go to solution for a wide range of materials and surfaces, ensuring a durable and aesthetically pleasing finish every time.



www.griffon.eu

Griffon. The choice of the pro.



# I CHOOSE POLY MAX<sup>®</sup> SEALANT ALL JOINTS BECAUSE...



#### "...IT CURES FAST AND IS EASY TO USE."

#### FEMKE, Builder 14 years of experience

It doesn't shrink and is durable. I love to create the perfect seal, the finishing touch. This is my solution for long lasting joints.

#### JAMES, Installer 24 years of experience

It cures fast and is easy to use. Poly Max<sup>®</sup> Sealant All Joints is water resistant after only 2 hours after application and this sealant can also be used on moist surfaces.

#### SANDRO, Contractor 30 years of experience

It's suitable for multiple sealing jobs. Whether I'm working indoor or outdoor, I can use the same product. Sanitary, kitchen and construction applications are all covered by this sealant.

## POLY MAX<sup>®</sup> SEALANT ALL JOINTS, THE CHOICE OF THE PRO!

## **INTERIOR**

For sealing gaps, seams and joints in walls, ceilings, window sills, stairs and skirting boards

- Paintable
- Does not shrink
- Permanently elastic
- Satin finish





### SANITARY

Seal baths, showers, sinks, toilets, shower drains & joints between walls and floors

- Suitable for natural stone and many other materials (even moist)
- Mildew resistant
- Waterproof
- Acid free

## EXTERIOR

Fill gaps, cracks, joints, (drill) holes and connecting or dilatation joints

- Waterproof
- Does not shrink
- Paintable
- UV and temperature resistant



### Technical specifications **POLY MAX® SEALANT ALL JOINTS**





### **SPECIFICATIONS**

| Colour             | White, Grey, Anthracite        | Transparent, Transparent-Grey, Black |
|--------------------|--------------------------------|--------------------------------------|
| Chemical basis     | SMP-Polymer                    | SMP-Polymer                          |
| Density            | Approx. 1.43 g/cm <sup>3</sup> | Approx. 1.05 g/cm <sup>3</sup>       |
| Tensile strength   | Ca. 150 N/cm <sup>2</sup>      | Ca. 150 N/cm <sup>2</sup>            |
| Hardness (Shore A) | Ca. 38                         | Ca. 32                               |

### **CURING TIMES\***

| Skin formation time | Approx. 10-15 min.      | Approx. 10-15 min.      |
|---------------------|-------------------------|-------------------------|
| Curing rate         | Approx. 2.5 mm/24 hours | Approx. 2.5 mm/24 hours |

### **PROPERTIES**

| Mildew resistance      | Very good            | Very good            |
|------------------------|----------------------|----------------------|
| Water resistance       | Very good            | Very good            |
| Temperature resistance | From -40°C to +100°C | From -40°C to +100°C |
| UV resistance          | Very good            | Very good            |
| Paintability**         | After appr. 2 hours  | After appr. 2 hours  |
| Elasticity             | Very good            | Very good            |
| Filling capacity       | Very good            | Very good            |
| Shelf life             | Min. 18 months       | Min. 18 months       |

#### Storage conditions

Properly sealed packaging should be stored on a dry, cool, frost free location at temperatures between +5°C and +25°C.

- Drying times may vary depending on surface, quantity of product applied, moisture content and ambient temperature, among other factors.
  \*\* Test beforehand

## FOR THE PERFECT FINISH

In addition to Griffon Poly Max<sup>®</sup> Sealant All Joints, Griffon is proud to introduce the Sealant Finisher, a ready-to-use and acid free primer that gives every sealant job a professional finish. Sealant Finisher has been specially developed to effortlessly smooth sealant joints, resulting in a perfect, even appearance. Sealant Finisher comes in a handy spray bottle made from 70% recycled plastic.

To complement the sealant concept, Griffon is also introducing the Sealant Finishing Set. This set with four spatulas is designed to finish all types of sealant joints. As the Sealant Finishing Set contains four different spatulas with rounded and square angles in different sizes, it is easy to finish almost all types of joints quick and tight. The Finishing Tools are made of thermoplastic rubber, making them long lasting and easy to clean.

### **SEALANT FINISHER**



## SEALANT FINISHING SET

Made of durable thermoplastic rubber

Multifunctional: for round joints, 45° & 90° joints and flat joints

Easy to clean – sealant residues are easily removed





www.griffon.eu





### FOR INTERIOR, SANITARY & EXTERIOR APPLICATIONS



Griffon. The choice of the pro.



### **GRIFFON IS A BRAND OF BISON INTERNATIONAL**

#### Griffon

Dr. A.F. Philipsstraat 9 P.O. Box 160 NL-4460 AD Goes Tel. +31 (0)113235700 Fax. +31 (0)113232077 info@griffon.eu www.griffon.eu

#### **SCAN FOR DETAILS**

