


**IMAL®**
**HIGH QUALITY PENETRATING OIL BASED ON GRAPHITE**

**TECHNICAL SPECIFICATIONS**

Chemical base:	Mineral oil with colloidal graphite
Colour:	Black

**STORAGE CONDITIONS**

Shelf life: At least 36 months after production.

Stored in unopened packaging between +5°C and +25°C.

Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

**PRODUCT DESCRIPTION**

High quality penetrating oil based on graphite.

**FIELD OF APPLICATION**

For loosening rusted and oxidised (assembling) materials, such as bolts, nuts, flanges, hinges and locks. Applicable on all metals. Also works preventively during assembly.

**PROPERTIES**

- Strongly penetrating
- Rust solving
- Rust and corrosion resistant
- With colloidal graphite
- With extra precision spray hose
- Can be used in all positions

**PREPARATION**

**Preliminary Surface Treatment:** Make sure that the surface is clean, dry, and free of grease.

**APPLICATION**
**Directions for use:**

Shake well before use.

Spray surface(s) generously from a distance of approx. 10-20 cm. After about 5 -10 minutes, the parts can be disassembled.

For preventive use parts must be treated first, then assembled.

**Stains/residue:** Remove stains with Griffon Primor or degreaser.

**Points of attention:** IMAL can cause irremovable stains in contact with clothing, etc. Use the additional spray hose integrated in the cap for optimum dosage.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.