



# ANTI-SPAT

## SILICONE-FREE WELDING SPRAY



### PRODUCT DESCRIPTION

Silicone-free welding spray.

### FIELD OF APPLICATION

For preventing adhesion of weld spatter on gun parts, clamps, brackets, burners, nozzles and equipment in MIG, MAG and CO<sub>2</sub> welding.

### PROPERTIES

- Silicone-free

### APPLICATION

#### Directions for use:

Shake well before use.

Spray welding torch, nozzle and object thinly and evenly from a short distance (approx. 20-30 cm). After welding, the weld spatter can be easily removed. Residues are easily removed with a degreaser.

**Points of attention:** Do not spray during welding. Do not spray on painted, varnished or synthetic surfaces. Keep aerosol out of reach of the welding spatters.

### TECHNICAL SPECIFICATIONS

|                |                        |
|----------------|------------------------|
| Chemical base: | Oil in organic solvent |
| Colour:        | Yellow (transparent)   |

### STORAGE CONDITIONS

Shelf life: At least 24 months after production.

Stored in unopened packaging between +5°C and +25°C.

Close packaging properly after use and store in a dry, cool, and frost-free location.

Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.