



DUCT TAPE MULTI-PURPOSE

HIGH-QUALITY, PROFESSIONAL, FIBRE-REINFORCED, UNIVERSAL TAPE



TECHNICAL SPECIFICATIONS

Carrier type:	LDPE
Chemical base:	Synthetic rubber
Initial tack:	Extremely high
Minimum temperature resistance:	-15 °C
Maximum temperature resistance:	60 °C
Peel adhesion:	SS 28 N/25mm
Rolling ball tack:	<3 cm
Tensile Strength (N/25 mm) approx.:	105 N/25 mm
Thickness (mm):	0.22 mm
Colour:	Grey

PRODUCT DESCRIPTION

High-quality, professional, fibre-reinforced, universal tape for fastening, sealing, insulating, repairing, protecting, fixing and bundling of virtually all materials.

FIELD OF APPLICATION

Suitable for sealing, insulating, repairing, protecting, strengthening, securing, mounting and joining many materials. Suitable for indoor and outdoor applications. Bonds on both smooth and rough surfaces, such as stone, concrete, wood and plastic.

PROPERTIES

- Very high adhesive strength
- Water resistant
- All-weather resistant
- UV resistant
- Vapour-proof
- Resistant to temperatures between -10°C and +75°C
- Hand tearable
- Airtight
- Pressure resistant up to 4 bar

PREPARATION

Working Conditions: Do not use in temperatures $\leq +5^{\circ}\text{C}$.

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of dust and grease. Remove any sharp and/or protruding parts.

APPLICATION

Directions for use:

Stick and press well the tape onto the object without touching the adhesive as this reduces the adhesive strength.

Stains/residue: Remove possible tape residue with white spirit.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.