



JITRASTRIP

SELF-ADHESIVE, ANTI-CORROSIVE, VULCANISING TAPE BASED ON BITUMEN WITH PE-FILM



TECHNICAL SPECIFICATIONS

Chemical base:	Bitumen
Colour:	Black
Material top layer:	PE
Minimum temperature resistance:	-25 °C
Maximum temperature resistance:	70 °C
Moisture resistance:	Very good
Thickness (mm):	1 mm
Water resistance:	Very good

STORAGE CONDITIONS

Shelf life: At least 24 months after production.

Close the container properly and store in a dry, cool and frost-free location. Opened packaging reduces the shelf life.

Limited shelf life after opening.

PRODUCT DESCRIPTION

Self-adhesive, anti-corrosive, vulcanising tape based on bitumen with PE-film.

FIELD OF APPLICATION

For the protection of, for instance, (underground) metallic conduits, connections, systems and installations. Also suitable for the protection, sealing and insulation of electrical connections, cables and plugs. Very simple to process, extremely suitable for uneven surfaces and/or shapes. Extremely suitable for vertical conduits.

PREPARATION

Working Conditions: Do not use at temperatures $\leq +10$ °C.

Preliminary Surface Treatment: In case of low temperatures, heat the substrate and/or tape with a gas burner or blow dryer.

Surfaces must be dry, clean, and free of dust and grease.

Remove loose paint traces and rust.

APPLICATION

Directions for use:

Remove the liner and apply under light pressure with 50% overlap and tool manually. Avoid air bubbles in overlapping strips. If surfaces are at an angle with each other, then press hard in the corner.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.